



- A Insulating grip see chart for color
- B Terminal male 99,995% zinc, different platings available
- C Nominal current OCR-A font
- D Test points
- E Nominal voltage imoulded

ELED ref.	RATING [A]	COLOR	VOLTAGE [V]
A320A	20	Yellow	32V
A325A	25	Grey	32V
A330A	30	Green	32V
A340A	40	Orange	32V
A350A	50	Red	32V
A360A	60	Blue	32V
A370A	70	Brown	32V
A380A	80	Natural	32V
A3100A	100	Violet	32V

FUSING TIME DIN 72581-3 ISO 8820-3		
LOAD [%]	MIN [s]	MAX [s]
100	360.000	-
135	60	900
160	10	200
200	2	60
350	0,2	7
600	0,04	1

UNLESS OTHERWISE SPECIFIED:  
 DIMENSIONS ARE IN MILLIMETERS  
 SURFACE FINISH:  
 TOLERANCES: 0,2  
 LINEAR:  
 ANGULAR:

FINISH:

DEBUR AND  
 BREAK SHARP  
 EDGES

DO NOT SCALE DRAWING

REVISION

**ELED** *On the safe side*

	NAME	SIGNATURE	DATE		
DRAWN	B.D.		12.2019		
CHK'D					
APPV'D					
MFG	www.eled.si				
Q.A				MATERIAL:	
				WEIGHT:	6g

TITLE:		<b>MAXI fuses family</b>  <b>A3XXA</b>		A4
DWG NO.				
SCALE:2:1		SHEET 1 OF 1		