



- A Insulating grip see chart for color
- B Nominal current stamped
- C Nominal current imoulded
- D Pcb LED element

ELED ref.	RATING [A]	COLOR
F1903	3	Violet
F1904	4	Pink
F1905	5	Tan
F1975	7,5	Brown
F1910	10	Red
F1915	15	Blue
F1920	20	Yellow
F1925	25	Natural
F1930	30	Green

FUSING TIME SAE J-1284		
LOAD [%]	MIN [s]	MAX [s]
110	360.000	-
135	0,75	1800
200	0,15	5
350	>0,08	-

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS SURFACE FINISH: TOLERANCES: 0,2 LINEAR: ANGULAR:				FINISH:	DEBUR AND BREAK SHARP EDGES	DO NOT SCALE DRAWING	REVISION																		
<table border="1"> <thead> <tr> <th>NAME</th> <th>SIGNATURE</th> <th>DATE</th> </tr> </thead> <tbody> <tr> <td>B.D.</td> <td></td> <td>12.2014</td> </tr> <tr> <td>CHK'D</td> <td></td> <td></td> </tr> <tr> <td>APPV'D</td> <td></td> <td></td> </tr> <tr> <td>MFG</td> <td></td> <td></td> </tr> <tr> <td>Q.A</td> <td></td> <td></td> </tr> </tbody> </table>						NAME	SIGNATURE	DATE	B.D.		12.2014	CHK'D			APPV'D			MFG			Q.A			TITLE:	
NAME	SIGNATURE	DATE																							
B.D.		12.2014																							
CHK'D																									
APPV'D																									
MFG																									
Q.A																									
						NORM LED fuses family																			
						DWG NO.	F1900																		
						SCALE:4:1	SHEET 1 OF 1																		
							A4																		