



- A Insulating grip see chart for color
- B Terminal male 99,995% zinc
- C Nominal current OCR-A font
- D Test points
- E Nominal voltage inmoulded
- F ISO standard inmoulded

ELED ref.	RATING [A]	COLOR	PLASTIC	OCR FONT	FORM
OA201A	1	Black	PC	1	E *
OA202A	2	Grey	PC	2	E
OA203A	3	Violet	PC	3	S
OA204A	4	Pink	PC	4	S
OA205A	5	Tan	PC	5	S
OA275A	7,5	Brown	PC	7.5	S
OA210A	10	Red	PC	10	S
OA215A	15	Blue	PC	15	Ω
OA220A	20	Yellow	PC	20	Ω
OA225A	25	Natural	PC	25	Ω
OA230A	30	Green	PC	30	Ω
OA235A	35	Dark green	PC	35	Ω
OA240A	40	Orange	PC	40	Ω

\* ISO 8820-3, 135% load not applicable for this rating

FUSING TIME DIN 72581-3 ISO 8820-3		
LOAD [%]	MIN [s]	MAX [s]
110	360.000	-
135	0,75	600
160	0,25	50
200	0,15	5
350	0,04	0,5
600	0,02	0,1

UNLESS OTHERWISE SPECIFIED:  
DIMENSIONS ARE IN MILLIMETERS  
SURFACE FINISH:  
TOLERANCES: 0,2  
LINEAR:  
ANGULAR:

FINISH:

DEBUR AND  
BREAK SHARP  
EDGES

DO NOT SCALE DRAWING

REVISION

**ELED** On the safe side

NAME	SIGNATURE	DATE	TITLE:
DRAWN	B.D.	12.2019	NORM OCR fuses family
CHK'D			
APPV'D			
MFG			
Q.A			
MATERIAL:		DWG NO.	OA2XXA
WEIGHT: 1,42g		SCALE:4:1	A4
		SHEET 1 OF 1	