



ELED Ref.	Rating	Color	Voltage
F1801	1A	Black	80V
F1802	2A	Grey	80V
F1803	3A	Violet	80V
F1804	4A	Pink	80V
F1805	5A	Tan	80V
F1875	7,5A	Brown	80V
F1810	10A	Red	80V
F1815	15A	Blue	80V
F1820	20A	Yellow	80V
F1825	25A	White	80V
F1830	30A	Green	80V
F1840	40A	Orange	80V

Breaking capacity 1000A @ 80V DC

Fusing time		
Load (%)	Minimum (s)	Maximum (s)
110 %	360.000	-
135 %	0,75	1.800
200 %	0,15	5
350 %	0,04	0,5
600 %	0,02	0,1

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN MILLIMETERS
SURFACE FINISH:
TOLERANCES:
LINEAR:
ANGULAR:

FINISH:

DEBURR AND
BREAK SHARP
EDGES

DO NOT SCALE DRAWING

REVISION

ELED *On the safe side*

NAME	SIGNATURE	DATE
DRAWN	B.D.	3.23
CHK'D		
APPV'D		
MFG		
Q.A		

TITLE:

Norm fuse 80V

DWG NO.

F1800

A4

WEIGHT:

SCALE:2:1

SHEET 1 OF 1